

Product Tech Sheet

SPECIFICATIONS

Model	Frequency Response	Signal-to-Noise Ratio	THD	Channel Separation	Input Range	DC Range	Fuse Rating
D3 400.2	20 - 20k Hz	>95 dB	<0.2%	50 dB (min.)	0.15 - 4V @ 20k ohms	10.2 - 15.5V	2 x 25 A
D3 500.4	20 - 20k Hz	>90 dB	<0.2%	50 dB (min.)	0.15 - 4V @ 20k ohms	10.2 - 15.5V	2 x 30 A
D3 600.1	40 - 250 Hz	>70 dB (40 to 250Hz)	<0.2%	n/a	0.15 - 4V @ 20k ohms	11 - 15.5V	3 x 25 A
D3 1000.1	40 - 250 Hz	>70 dB (40 to 250Hz)	<0.2%	n/a	0.15 - 4V @ 20k ohms	11 - 15.5V	4 x 30 A

PHYSICAL DIMENSIONS

Model	(A) Length	(B) Width	(C) Height	Weight
D3 400.2	15"	8.5"	2.3125"	12.1 lbs
D3 500.4	14.5"	8.5"	2.3125"	12.6 lbs
D3 600.1	14.875"	8.5"	2.3125"	13.3 lbs
D31000.1	15.875"	8.5"	2.3125"	14.4 lbs

RMS POWER

Model	4 Ohm Stereo	2 Ohm Stereo	4 Ohm Mono	2 Ohm Mono	1 Ohm Mono
D3 400.2	100 x 2	200 x 2	400 x 1	n/a	n/a
D3 500.4	75 x 4	125 x 4	250 x 2	n/a	n/a
D3 600.1	n/a	n/a	250 x 1	400 x 1	600 x 1
D3 1000.1	n/a	n/a	400 x 1	600 x 1	1000 x 1

